



System

CPU-Intel P4 Processor	Pentium M (PGA) 1.3GHz ~ 2.0GHz Celeron M LV/ ULV BGA Processor
Cache Memory	2nd Level depend on CPU
System Chipset	Intel 915GM+ICH6
System Memory	Default 256MB, maximum up to 2GB
Compact Flash	Support Compact Flash Card
HDD Driver	Built-in 2.5" SATA HDD bay
Audio	Integrated stereo (2W + 2W) speakers RFID, WIFI, Bluetooth
Optional UPS	Battery Pack (5 minutes run time after power loss)
Construction	Magnesium-Aluminum & Aluminum
O/S Support	Die-casting Housing Win2000, XP Pro, XP Embedded, WEPOS and Linux

Main Display

Chipset	GMA900
Memory Size	Share System Memory, 32MB
Resolution Size	15" TFT LCD / 1024 x 768
Brightness	250 cd/m ² (Adjustable)
Touch Screen	ELO 5-wire Resistive Touch
Optional Peripherals	2-in-1 (MSR + Finger print)

I/O Connectivity

Serial Port	4 x External : COM1, COM2, COM5 (D-SUB9) COM6 (RJ-45) 2 x Internal : COM3 for Touch screen, COM4 for VFD
Parallel Port	1 x Bi-directional Parallel (D-SUB25)
Standard USB Port	7 x USB 2.0 - 3 x internal - 4 x external Front side X 1 Rear side X 4 (12V Power USB X1, 5V Power USB X1)
Audio Port	Line-out
Cash Drawer Port	1 x 12V / 24V Cash Drawer RJ11 connector (single / dual)
PS/2 Keyboard Port	N/A (for Optional peripherals only)
Ethernet	1 x RJ45 10/100/1000 Base-T

Customer Display (Optional)

LCD Display	15" TFT LCD (Resistive Touch / Non-touch)
VFD	VFD Display

Mechanical and Environment

Dimensions(W x H x D)	379.40 x 386.60 x 300.00 mm
Housing Color	Silver, Black, Silver / Blue, Red / Black, Silver/Black
Weight	14Kg (include one VFD)
Operating Temperature	0° ~ 35°
Power Supply	120W 19 V Power Adapter
EMI/Safety	CE, FCC, UL, RoHS